

EJOFAST® self-drilling screw JF3-2H-4.8



Cross references

Socket wrench insert
Cordless screwdriver ASCS 6.3

Application range


- > Side lap stitching of profiled steel / aluminium sheets and sandwich panel
- > Suitable for installation with the EJOFAST® JF screwdriver

Properties


- > A2 stainless steel with hardened steel drill point
- > Stainless steel sealing washer
- > Pre-assembled sealing washer
- > With free spin zone under screw head for side lap stitching
- > Non-skid application
- > Fastening without swarf*
- > Loose or collated

***Without swarf** means that - contrary to conventional self-drilling screws with classic cutting bit - ribbon swarfs, spiral swarfs or spiral swarf pieces are avoided.

Applications



Technical data



EJOFAST® JF screwdriver
available as rental equipment.

Certifications



Online shop



Order description	Length [mm]	Diameter [mm]	Clamp thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Sealing washer E 14, Ø 14 mm, loose							
JF3-2H-4.8x19-E14	19	4.8	0 - 4	500		3 591 977 391	4061245015583
JF3-2H-4.8x19-E14 VE100	19	4.8	0 - 4	100		6 591 977 391	4061245014791
JF3-2H-4.8x19-E14 RAL 7016	19	4.8	0 - 4	100		3 351 977 025	4061245039749
JF3-2H-4.8x19-E14 RAL 9002	19	4.8	0 - 4	100		3 351 977 082	4061245039671
JF3-2H-4.8x19-E14 RAL 9006	19	4.8	0 - 4	100		3 351 977 084	4061245044804
JF3-2H-4.8x19-E14 RAL 9007	19	4.8	0 - 4	100		3 351 977 220	4061245044811
Sealing washer E 14, Ø 14 mm, collated							
JF3-2H-4.8x19-E14 collated	19	4.8	0 - 4	500		3 385 009 000	4061245016559