

## EJOT Dabo® screw TKR-4-4.8



### Application range

- > To fix roofing membranes to substructures made of sheet steel  $\geq 1.5 \text{ mm} \leq 4.0 \text{ mm}$
- > For combination with EJOT stress plates


### Properties

- > Case-hardened steel
- > Climadur coated – high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)
- > Can be delivered belted for EJOT installation tool ECOSET or pre-assembled with EJOT stress plate HTK-2G for EJOT installation tool ECOSET HTK.
- > With bugle head

### Applications



### Technical data



### Certifications



### Cross references

Stress plate HTV 82/40 TK  
 Stress plate HTV 82/40 F  
 Stress plate HTV 40 RU  
 Stress plate HTK-2G 50  
 Stress plate EcoTek 50  
 Stress plate HTK-S  
 Flat roof profile FP  
 Installation tool ECOSET  
 Installation tool ECOSET HTK  
 Bit cross recess

### Length determination (min. lengths)

Sheet steel	Insulation thickness + 20 mm
Timber	Insulation thickness + 30 mm



EJOT® installation tool ECOSET available as rental equipment.

### Online shop



Order description	Length [mm]	Diameter [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
TKR-4-4.8x70	70	4.8	500		3 438 070 639	4061245012438
TKR-4-4.8x90	90	4.8	500		3 438 090 639	4061245012421
TKR-4-4.8 x110	110	4.8	250		3 438 110 639	4061245012414

### Compatibility acc. to ETA-07/0013

	HTV 82/40	HTE 82/40	HTV 82/40 TK	HTV 82/40 F	HTV 40 RU	HTK 2G 50xL	HTK 2G 75xL	EcoTek 50	EcoTek-T 50	HTK-S	Flat roof profile FP
<b>TKR-4-4.8</b>			X	X	X	X	X	X	X	X	X