

Window screw type Super-E



Cross references

Bit cross recess H2

Application range

- > Fastening of tilt and turn fittings in PVC profiles and in steel or GRP inserts
- > Fixing locking plates, strips and bearings


Properties

- > Case-hardened steel
- > Cost-effective screw for fittings with one-start thread
- > Under-head serrations for increased safety against stripping
- > Slightly curved head for flawless appearance even with bevelled installation
- > Roll-sorted quality for automated fastening
- > EJOSEAL is an inorganic, transparent sealant, to significantly increase the corrosion and heat resistance of fastening elements with zinc or zinc alloy coatings. EJOSEAL does not contain wax and is ideally suitable for direct fastening into plastic.

Processing information

- > Can also be fastened in steel, pre-drilling required (see chart)
- > Can also be fastened in GRP, pre-drilling might be required

Technical specifications



| Sheet thickness | Pre-drilling diameter |
|-----------------|-----------------------|
| 1.5 mm | 3.0 mm |
| 2.0 mm | 3.0 mm |
| 2.5 mm | 3.0 mm |

Product online



| Order description | Length [mm] | PU [pieces] | Price/100 [EUR] | Article number | EAN |
|-----------------------------|-------------|-------------|-----------------|----------------|---------------|
| EJOSEAL | | | | | |
| Window screw Super-E 4.2x16 | 16 | 1000 | | 2253416607 | 4061245041438 |
| Window screw Super-E 4.2x20 | 20 | 1000 | | 2253420607 | 4061245041421 |
| Window screw Super-E 4.2x22 | 22 | 1000 | | 2253422607 | 4061245041414 |
| Window screw Super-E 4.2x25 | 25 | 1000 | | 2253425607 | 4061245041407 |
| Window screw Super-E 4.2x28 | 28 | 1000 | | 2253428607 | 4061245041391 |
| Window screw Super-E 4.2x30 | 30 | 1000 | | 2253430607 | 4061245041384 |
| Window screw Super-E 4.2x35 | 35 | 1000 | | 2253435607 | 4061245041377 |
| Window screw Super-E 4.2x40 | 40 | 1000 | | 2253440607 | 4061245041360 |
| Window screw Super-E 4.2x45 | 45 | 1000 | | 2253445607 | 4061245041353 |
| Window screw Super-E 4.2x55 | 55 | 1000 | | 2253455607 | 4061245041346 |