

GRIPPER all-wall plug



Cross references

Cordless screwdriver
ASCM QSW
Hammer drill SDS plus®

Application range

- > For pre-positioned installation in boards, cavity and solid walls as well as in any other construction material

Application examples

- > Hand rails
- > Wall attachment of cabinets
- > Ceiling lights
- > Storage racks
- > Bookcases
- > Mounting televisions
- > Radiators
- > Wash basins
- > Urinals
- > Electrical installations
- > Attachment of HVAC and sanitary equipment
- > Attachment of sanitary equipment

Properties

- > Plug made of thermoplastic elastomer - the material adapts to the surface of the drill hole, while the non-slip GripEdge surface and the screws ensure secure mechanical embedment
- > GRIPPER surpasses normal plugs in its power of resistance against long-term stress, wear, weather conditions, moisture and storage
- > Can be used with all common types and diameters of screws
- > The special collar keeps the plug at the optimal installation depth and also remains covered by the screw head

Appropriate screws	Diameter [mm]	Length [mm]
GRIPPER 6	4- 5.5	32 + t _{fix}
GRIPPER 8	4.5-6	38 + t _{fix}
GRIPPER 10	4.5-7	45 + t _{fix}

Applications






Base materials

Suitable for

- > Aerated concrete block
- > Plasterboard
- > High-strength plasterboard
- > Hollow light expanded clay aggregate block
- > Pre-stressed hollow core slab
- > Natural stone
- > Non-cracked concrete
- > vertically perforated brick
- > Perforated sand-lime brick
- > Solid clay brick
- > Solid light expanded clay aggregate block
- > Solid sand-lime brick

Applications



Product online



Order description	L [mm]	d ₀ [mm]	h ₁ ≥ [mm]	t _{sheet, min} [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Gripper 6 all wall plug	32	6	38	8	100		9650075232	4061245003146
Gripper 8 all wall plug	38	8	44	12	50		9650075234	4061245003139
Gripper 10 all wall plug	45	10	50	12	50		9650075236	4061245003122