

NEW Self-drilling screw JT2-ST-2-6.8 EJO GUARD**Application range**



- > Fastening milled system rails to thin-walled steel and aluminum substructures
- > To fix roofing membranes and insulating material to substructures made of sheet steel ≥ 0.70 in mm ≤ 1.5 mm, timber or wood-based material in combination with EJOT stress plates

Properties

- > Case-hardened steel, protected against corrosion
- > EJO GUARD corrosion protection
- > With countersunk head

Cross references

Stress plate HTV 82/40 F
 Stress plate HTV 40 RU
 Flat roof profile FP
 Stress plate EcoTek 50
 Cordless screwdriver ASCM QSW
 Bit hexalobular TX25
 Bit holder

Applications**Technical specifications****Certifications****Installation process****Product online**

Order description	Length [mm]	Thread length [mm]	Clamping thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT2-ST-2-6.8x205 EJO GUARD	205	75	130–195	100		7282305609	4061245014425
JT2-ST-2-6.8x245 EJO GUARD	245	75	170–235	100		7282345609	4061245014401
JT2-ST-2-6.8x285 EJO GUARD	285	75	210–275	100		7282385609	4061245014395
JT2-ST-2-6.8x325 EJO GUARD	325	75	250–315	100		7282335609	4061245014418