

## ISO-BLOCO 300



### Product description

ISO-BLOCO 300 is a PUR sealing tape impregnated with polymer dispersion. In its compressed state it is a reliable seal against driving rain, dust and drafts. With the appropriate compression, it offers a reliable protection against driving rain to a minimum of 300 Pa. Equivalent to strong gale 9 wind force, ISO-BLOCO 300 is also a thermal and acoustic insulation. It meets the high qualification requirements for the BG2 classification, in accordance with DIN 18542 issue 2009.

### Application range

- > For sealing joints and connections in building construction and facades
- > For applications including windows, metal, masonry, wood and drywall
- > Can be used as a thermal barrier tape

### Benefits

- > Complies with the DIN 18542 BG 2
- > Seals against wind, dust, splash water and driving rain
- > Permanently elastic with long-term movement absorption
- > Vapour diffusion permeable
- > Thermal and acoustic insulation
- > Can be painted over with standard emulsion paints
- > Good adhesive properties, to aid installation
- > Constant quality control according to DIN standards, with regular controls from independent institutions

Order description	Dimension joint depth x width [mm]	Box content [rolls]	Metres per roll [m]	PU [m]	Price/100 m [EUR]	Article number	EAN
ISO-BLOCO 300 10 / 1-4	10 / 1-4	30	13.0	390		0030010104	4048368258912
ISO-BLOCO 300 15 / 1-4	15 / 1-4	20	13.0	260		0030015104	4048368258929
ISO-BLOCO 300 15 / 2-6	15 / 2-6	20	12.0	240		0030015206	4048368258387
ISO-BLOCO 300 15 / 4-9	15 / 4-9	20	8.0	160		0030015409	4048368258417
ISO-BLOCO 300 20 / 1-4	20 / 1-4	15	13.0	195		0030020104	4048368258936
ISO-BLOCO 300 20 / 2-6	20 / 2-6	15	12.0	180		0030020206	4048368258394
ISO-BLOCO 300 20 / 4-9	20 / 4-9	15	8.0	120		0030020409	4048368258424

**\* Movement of structural elements and temporary changes in length of existing joints have to be taken into account for the suitable tape dimensions.**