

DEKTITE® Combo Set



Cross references

Joint sealant
Tightener
Hose clamp

Application range

- > For sealing pipes on metal or fiber cement roofs
- > For subsequent waterproofing of pipes

Properties

- > Version EDPM (black)
- > Temperature resistance EPDM (black or grey) permanent 50 °C to +115 °C, short-term up to +150 °C
- > Temperature resistance silicone (red) permanent 50 °C to +200 °C, short-term up to +250 °C

Advantages

- > Perfect seal on roof and facade
- > No interference of thermal elongation of pipes
- > No fatigue fractures
- > Ideal for repairs of existing pipe systems
- > 20-year warranty on material

Notice

Use folding blind rivets for fibre cement boards.
Profile height max. 45 mm.

Included in delivery

- 1 pipe flashing
- 1 cartridge of EJOPLAST joint sealant
- 1 self-drilling screw set - optionally folding blind rivet set
- 1 clips set

Assembly instruction



Product online



Order description	For pipe diameter [mm]	Base [mm]	Roof pitch [°]	Content Cartridge [ml]	Content Screws [pieces]	PU [set]	Price/1 [EUR]	Article number	EAN
DC 101 B Set	5–60	139 x 139	0–40	80	8	1		8201104704	4061245046846
DC 103 B Set	5–127	218 x 218	0–40	80	16	1		8201304704	4061245046853
DC 104 B Set	75–175	285 x 285	0–40	80	20	1		8201404704	4061245046860
DC 106 B Set	125–230	365 x 365	0–40	80	28	1		8220304704	4061245046877
DC 107 B Set	150–280	454 x 454	0–40	310	32	1		8230304704	4061245046884
DC 109 B Set	240–503	685 x 685	0–40	310	40	1		8250304704	4061245046891
DC 110 B Set	350–760	1000 x 1040	*	310	70/10	1		8270004704	4061245013572

*350 - 500 mm cut: maximum 30°; 500 - 760 mm cut: maximum 15°

Order information: All versions also available in grey (EPDM) and red (silicone) Further lengths upon request.