

Flat roof profile FP



Cross references

Self-drilling screw JT2-ST-2-6.0
 Self-drilling screw JT3-ST-2-6.0
 DABO® SW8-RT-4.8
 DABO® SW8-ET-4.8
 DABO® TKR-4.8
 DABO® TKE-4.8
 DABO® TKR-4-4.8
 DABO® VHT-R-4.8
 DABO® VHT-E-4.8
 Concrete screw FBS-R
 Aerated concrete screw FPS-E
 Stress plate HTK-S
 Universal anchor SDF-S-10H-E
 Universal anchor SDP-S-10G-E

Application range

- > To fix roofing membrane and insulating material to substructures made of concrete, aerated concrete, steel, aluminium trapezoidal profile, timber and wood-based materials.
- > For structural fastening of the edges
- > For fastening the edges of roofing membranes on wall connections and roof edges

Properties

- > Alu-zinc-coated steel
- > Metal rail fastening system
- > Easy processing
- > 3 different hole diameters combined in one profile
- > Flexible application possibilities


Notice

For combination with EJOT DABO® screws, concrete and aerated concrete screws and self-drilling screws. For combination with facade anchors according to ETA-10/0305.

Technical specifications

Material thickness	1.5 mm
Hole diameter for stress plate HTK-S	14.5 mm
Hole diameter for facade anchors	10.5 mm
Hole diameter for screws	7.0 mm

Applications



Technical specifications



Certifications



For an approved application in the area of wall connections on the roof parapet (concrete and aerated concrete)

Product online



Order description	Length [m]	Width [mm]	PU [m]	Price/m [EUR]	Article number	EAN
EJOT FP FLD profile	2.25	30	27		7999001886	4061245011653

Compatibility acc. to ETA-07/0013

SW 8 RT-4.8	•
SW 8 ET-4.8	•
TKR-4.8	•
TKE-4.8	•
TKR-4-4.8	•
VHT-R-4.8	•
VHT-E-4.8	•
JT2-ST-2-6.0	•
JT3-ST-2-6.8	•
JT3-ST-2-6.0	•
FBS-R-6.3	•
JBS-R-7.5	•
FPS-E-8.0	•
SDF-S-10H-E	•
SDP-S-10G-E	•

Flat roof profile FP