

## Self-drilling screw JT9-3H/5-5.5x19



### Cross references

Cordless screwdriver  
ASCM QSW  
Socket wrench insert SW8

### Application range

- > To form sliding and fixed points on substructures of rainscreen facades
- > Fastening pre-drilled stainless steel or aluminium wall brackets with aluminium support profiles
- > For component assemblies from 3.1 – 5.0 mm (component I + component II)

### Properties

- > A4 stainless steel

### Notice

Component assemblies checked with  $R_m$  (component II)  $\geq 190$ ,  $\geq 215$  and  $\geq 245$  N/mm<sup>2</sup>. For bearing values, please refer to the building authority test certificate (abP) P-BWU02-1980001.


### Possible part combinations

Component I [mm]	Component II [mm]	$R_m$ support profile/ Wall bracket
	1.6	
1.5 (stainless steel)	2.0	$\geq 190$ N/mm <sup>2</sup> (aluminium)
	2.4	
3.0 (aluminium)	1.6	
	2.0	

### Applications



### Technical specifications



### Certifications



### Product online



### Order description

Order description	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT9-3H/5-5.5x19	19	500		7380540340	4061245014272
JT9-3H/5-5.5x19 VE100	19	100		6380540340	4061245014869